Kindermann®
proudly presents

Klick&Show

K-40

Just present the way you like: with or without WiFi transmitter – with or without PC-client – all mixed in the same meeting!

> **Universal**, cross-platform wireless solution for BYOD presentation
> **BYOD** – Present wirelessly via transmitter, Apps for Windows, MacOS, Android or via AirPlay, Miracast and Google Cast
> **Best picture quality** via HDMI output in 4K60 resolution
> **Split-Screen function** for simultaneous presentation of up to 4 participants on the main display
> **2 types of Klick&Show 4K transmitters** are available to choose from: HDMI and USB-C
> **Add more transmitters** to include more participants in the meeting and to increase device compatibility
> **Full enterprise network integration** possible, with total control for administrators via the built-in web interface or the free ManageTool
> **Intuitive-to-use** and secure

Klick&Show K-40 Base Unit is a universal wireless presentation system, which perfectly fits into meeting rooms, huddle spaces as well as class- and training rooms, supporting BYOD (Bring your own device). Klick&Show allows users to share audio-visual content from their laptops or mobile devices in a simple way – with no cables, no hassle, and no wasted time.

Complete your Klick&Show system with the matching Klick&Show 4K WiFi transmitters. Simply connect a transmitter to your device and click the Show button to mirror live content to the main screen. Keep your meeting table perfectly organized with the TRAY-4K in a matching design.

Laptop users without transmitter simply launch the Klick&Show client App for Windows or MacOS to mirror content to the main screen. Content from mobile phones and tablets can be shared just as easily via AirPlay, Miracast, Google Cast or via the free Android App.

Details

Technical specifications	K-40
Wireless mirroring of screen content (BYOD)	Yes
Wireless transmission of USB camera/audio (BYOM)	-
Compatible transmitters	HDMI, USB-C, 4K HDMI, 4K USB-C, USB-A
Windows 10 / 11	Transmitter / Klick&Show App for Windows / Google Cast / Miracast (with optional Miracast USB WiFi adapter)
macOS	Transmitter / Klick&Show App for macOS / AirPlay / Google Cast
Mobile devices	USB-C transmitter (DP ALT mode required) / Android App / AirPlay / Google Cast / Miracast (with optional Miracast USB WiFi adapter)
Miracast support	optional, supports Miracast-Direct (P2P) and Miracast-over-Infrastructure (MS MICE)
Maximum resolution, wireless	4K: with 4K transmitter; 1080p: with Full-HD transmitter / Klick&Show App / Airplay / Miracast / Google Cast
Simultaneous connections RJ45	more than 30
Simultaneous connections internal WLAN	up to 16
Splitscreen	up to 4 simultaneously, layout adjustable
Low latency mouse cursor	yes, USB-A* transmitter and Klick&Show App for Windows / macOS
Touch-back / USB-HID support	yes, e.g. for use with interactive displays (touchscreens), whiteboards or projectors
WiFi frequency band	2.4 / 5 GHz
WiFi standard	WiFi 5 (IEEE 802.11b/g/n/ac)
WiFi antennas	2×2 MIMO
WiFi bandwidth	up to 1200 Mbps
Security standard	WiFi: WPA PSK, WPA2 PSK - Video transmission encrypted with AES-256 bit + RSA1024 bit
HDMI output	1× HDMI 2.0 / 3840×2160@60/30 Hz, 1920×1080@60Hz, 1280×720@60Hz
HDCP version	HDCP 1.4, HDCP 2.0
HDMI input / max. resolution	via HDMI transmitter (4K30 or 1080p60)
Audio input	Transmitter / Klick&Show App / AirPlay / Google Cast / Miracast (with optional Miracast USB WiFi adapter)
Audio output (analog)	1× 3.5 mm stereo jack
USB 2.0 (type C)	1× (front)
USB 2.0 (type A)	1× (front)
USB 3.0 (type C)	-
USB 3.0 (type A)	1× (rear)
USB 3.0 (type B)	-
LAN (RJ45)	IEEE802.3af
PoE standard	Network: Web GUI, Telnet; RS232: 1× 3-pin Euroblock (rear)
Control	Network: Web GUI, Telnet; RS232: 1× 3-pin Euroblock (rear); 2× GPI: 1× 3-pin Euroblock (rear)
Power consumption	max. 18 W
Part number	**7488000330**

*no longer available since August 2023

More informations
Visit our website for more information

Subject to change in the interest of progress. Illustrations and technical specifications may contain additional options and are not binding for the design. All dimensions are subject to the usual tolerances.

proudly presented by:

Kindermann GmbH
Mainparkring 3 | 97246 Eibelstadt | Germany
Tel. +49 9303 9840-0 | Fax +49 9303 9840-101
Printed in Germany | 03/26 | 0101006002

www.kindermann.com